

Poulie dentée monobloc profil T10

Pas 10 mm pour courroie largeur 25 mm

MATIÈRE

- Aluminium 6082-T6 UNI 9006.

Illustration technique et photo, voir page 318.

		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	Référence
												
Aluminium												
A9-40T10-12F	●	6F	12	6	42	38,20	36,35	28	40	30	0,1	Exemple de commande A9-40T10-12F
A9-40T10-14F	●	6F	14	8	48	44,56	42,7	32	40	30	0,13	
A9-40T10-15F	●	6F	15	8	51	47,75	45,9	32	40	30	0,15	
A9-40T10-16F	●	6F	16	8	54	50,93	49,1	35	40	30	0,18	
A9-40T10-18F	●	6F	18	8	60	57,30	55,45	40	40	30	0,22	
A9-40T10-19F	●	6F	19	8	66	60,48	58,65	44	40	30	0,25	
A9-40T10-20F	●	6F	20	8	66	63,66	61,8	46	40	30	0,28	
A9-40T10-22F	●	6F	22	8	75	70,03	68,2	52	40	30	0,34	
A9-40T10-24F	●	6F	24	8	83	76,39	74,55	58	40	30	0,39	
A9-40T10-25F	●	6F	25	8	83	79,58	77,75	60	40	30	0,42	
A9-40T10-26F	●	6F	26	8	87	82,76	80,9	60	40	30	0,48	
A9-40T10-27F	●	6F	27	8	91	85,94	84,1	60	40	30	0,54	
A9-40T10-28F	●	6F	28	8	93	89,13	87,25	60	40	30	0,55	
A9-40T10-30F	●	6F	30	8	97	95,49	93,65	60	40	30	0,64	
A9-40T10-32F	●	6F	32	10	106	101,86	100	65	40	30	0,69	
A9-40T10-36F	●	6F	36	10	119	114,59	112,75	70	40	30	0,87	
A9-40T10-40F	●	6F	40	10	131	127,32	125,45	80	40	30	1,07	
A9-40T10-44F	●	6	44	10	-	-	138,2	88	40	30	1,35	
A9-40T10-48F	●	6	48	16	-	-	150,95	95	40	30	1,52	
A9-40T10-60F	●	6	60	16	-	-	189,15	110	40	30	2,34	

● Délai maîtrisé ○ Contactez-nous

Exemple de commande **A9-40T10-12F**

**Produits
associés**


A8-25-T10
Page 244



MIDAS A9-T10
Page 335



A8-25T10-PU
Page 252