


# Poulie dentée monobloc profil AT5

**Pas 5 mm** pour courroie largeur 16 mm

**MATIÈRE**

- Aluminium 6082-T6 UNI 9006.
- Flasques en acier galvanisé.

Illustration technique et photo, voir page 318.

	● Délai maîtrisé ○ Contactez-nous												Référence
		Schéma	Nombre de dents	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	l <sub>1</sub>	l <sub>2</sub>	Poids kg		<b>A9-27AT5-12F</b>
A9-27AT5-12F	●	6F	12	-	23	19,1	17,85	10	27	21	0,02		
A9-27AT5-14F	●	6F	14	-	25	22,28	21,05	13	27	21	0,03		
A9-27AT5-15F	●	6F	15	-	28	23,87	22,65	16	27	21	0,03		
A9-27AT5-16F	●	6F	16	-	32	25,46	24,2	18	27	21	0,04		
A9-27AT5-18F	●	6F	18	-	32	28,65	27,4	20	27	21	0,04		
A9-27AT5-19F	●	6F	19	-	36	30,24	29	22	27	21	0,05		
A9-27AT5-20F	●	6F	20	-	36	31,88	30,6	23	27	21	0,06		
A9-27AT5-22F	●	6F	22	-	38	35,01	33,85	24	27	21	0,06		
A9-27AT5-24F	●	6F	24	-	42	38,2	37	26	27	21	0,08		
A9-27AT5-25F	●	6F	25	-	44	39,79	38,55	26	27	21	0,08		
A9-27AT5-26F	●	6F	26	-	44	41,38	40,2	26	27	21	0,09		
A9-27AT5-27F	●	6F	27	8	48	42,97	41,8	30	27	21	0,09		
A9-27AT5-28F	●	6F	28	8	48	44,56	43,35	32	27	21	0,09		
A9-27AT5-30F	●	6F	30	8	51	47,75	46,55	34	27	21	0,1		
A9-27AT5-32F	●	6F	32	8	54	50,93	49,7	38	27	21	0,12		
A9-27AT5-36F	●	6F	36	8	63	57,3	56,05	38	27	21	0,16		
A9-27AT5-40F	●	6F	40	8	66	63,66	62,45	40	27	21	0,19		
A9-27AT5-42F	●	6F	42	8	71	66,84	65,6	40	27	21	0,2		
A9-27AT5-44	●	6	44	8	-	70,03	68,8	45	27	21	0,23		
A9-27AT5-48	●	6	48	8	-	76,39	75,15	50	27	21	0,28		
A9-27AT5-60	●	6	60	8	-	95,49	94,25	65	27	21	0,43		

■ Exemple de commande **A9-27AT5-12F**

**Produits associés**



**A8-16-AT5**  
Page 248



**A8-16AT5-PU**  
Page 252