

Poulie dentée à moyeu amovible

Pas 12,7 mm (1/2") pour courroie largeur 25,4 mm


Illustration technique et photo, voir pages 282 / 283.

MATIÈRE

- Acier.
- Fonte.

Référence
Exemple de commande A9-16H100-1108

● Délai maîtrisé ○ Contactez-nous

		Schéma	Nombre de dents	Alésage maxi du moyeu	d ₂	d ₃	d ₄	d ₅	d ₆	l ₁	l ₂	l ₃	Poids kg
Acier													
A9-16H100-1108	●	5F	16	28	71	64,68	63,31	-	45	22	31	9	0,42
A9-18H100-1210	●	5F	18	32	79	72,77	71,39	-	52	25	31	6	0,49
A9-19H100-1210	●	5F	19	32	83	76,81	75,44	-	56	25	31	6	0,62
A9-20H100-1210	●	5F	20	32	87	80,85	79,48	-	60	25	31	6	0,73
A9-21H100-1210	●	5F	21	32	91	84,89	83,52	-	64	25	32	7	0,8
A9-22H100-1210	●	5F	22	32	93	88,94	87,56	-	67	25	32	7	0,94
A9-23H100-1610	●	5F	23	42	97	92,98	91,61	-	70	25	32	7	0,97
A9-24H100-1610	●	5F	24	42	103	97,02	95,65	-	73,5	25	32	7	1,05
A9-25H100-1610	●	5F	25	42	106	101,06	99,69	-	77	25	32	7	1,1
A9-26H100-1610	●	5F	26	42	111	105,11	103,73	-	82	25	32	7	1,2
A9-27H100-1610	●	5F	27	42	115	109,15	107,78	-	85	25	32	7	1,35
A9-28H100-1610	●	5F	28	42	119	113,19	111,82	-	90,5	25	32	7	1,5
A9-30H100-1610	●	5F	30	42	127	121,28	119,9	-	98	25	32	7	1,78
A9-32H100-1610	●	5WF	32	42	135	129,36	127,99	90	106	25	32	7	2,05
A9-36H100-1610	●	5WF	36	42	152	145,53	144,16	92	121	25	32	7	2,8
A9-40H100-1610	●	5WF	40	42	168	161,7	160,33	92	138	25	32	7	3,65
A9-44H100-2012	●	3WF	44	50	184	177,87	176,5	106	152	32	32	-	3,86
A9-48H100-2012	●	3WF	48	50	200	194,04	192,67	106	169	32	32	-	4,2
Fonte													
A9-60H100-2012	●	9A	60	50	-	242,55	241,18	106	223	32	34	1	3,76
A9-72H100-2012	●	9A	72	50	-	291,06	289,69	106	270	32	34	1	4,88
A9-84H100-2012	●	9A	84	50	-	339,57	338,2	106	318	32	34	1	6,12
A9-96H100-2517	●	7A	96	60	-	388,08	386,71	119	366	45	34	5,5	7,95
A9-120H100-2517	●	7A	120	60	-	485,1	483,73	119	462	45	34	5,5	10,05

Produits associés

A9-MA Page 520

A8-H100 Page 228

A8-H100-CH
Page 255

A9-H100 Page 274